



# **BUCKET FORKS**

## **SHAFT-MOUNTED BUCKET FORKS**

### **LIP-MOUNTED BUCKET FORKS**

#### **SHAFT-MOUNTED BUCKET FORKS** **TURN YOUR LOADER BUCKET INTO A FORKLIFT**

Rockland Shaft-Mounted Bucket Forks turn your loader into a forklift. Equip your tractor loader backhoe or wheel loader with bucket forks to handle pallets, load lumber, pipe, and roofing materials. Do it all with just one machine. When it is time to use the bucket, the operator simply drops the forks without leaving his seat.

Rockland Shaft-Mounted Bucket Forks feature solid steel tines, a solid steel shaft, adjustable fork spacing, as well as the ability to mount the forks in just minutes. You can also equip similar sized machines with mounting brackets to allow a second or third machine to use the same set of forks. Lower your costs and lift your profits by making your machines more versatile with Rockland Shaft-Mounted Bucket Forks.



#### **LIP-MOUNTED BUCKET FORKS** **CLAMPS TO ANY BUCKET**

Rockland Lip-Mounted Bucket Forks are a quick, easy, and inexpensive way to turn your loader bucket into a forklift. Lip-Mounted forks feature solid steel tines, a built-in clamp and an extended tine riser which prevents loads from moving backward while traveling. Lip-Mounted bucket forks can be used on any similar sized loader. Increase the productivity of your loader with the addition of Rockland Lip-Mounted Bucket Forks.



# BUCKET FORK SPECIFICATIONS

## SHAFT-MOUNTED

[Click here to identify your machine category.](#)

Category	Skid Steer	TLB, 5		10		20		30		40		50, 60		70
Rated Tine Capacity	2000	4000		6000		7000		10,000		10,000	15,000	15,000	25,000	25,000
Back Height	36"	41"	47"	54"		54"		68"		68"	72"	72"	87"	87"
Max. Width Over Tines	55"	76"		76"		76"		76"		76"		76"	96"	96"
# of Brackets	3	3		4		4		4		4		4	5	5
Tine Length	36"	42"		45"	60"	45"	60"	48"	60"	48"	52"	52"	72"	72"
Tine Size	1x4	1.25x4		1.75x5		1.75x5		2x5	2x6	2x5	2x8	2x8	5x8	5x8
Weight lbs.	230	350	365	650	675	650	675	925	1120	925	1360	1360	1985	1985

Specifications subject to change without notice.

## LIP-MOUNTED

[Click here to identify your machine category.](#)

Category	Skid Steer	TLB, 5	10	20
Rated Tine Capacity	2000	4000	6000	8000
Tine Length	36"	42"	48"	48"
Max. Lip Thickness For Clamp	2.5"	2.5"	3.5"	3.5"
Weight lbs.	175	225	325	400

Specifications subject to change without notice.

## MOUNTING INFORMATION

**Shaft-mounted** - The bucket fork kit includes two tines, a solid steel shaft, and mounting brackets.

**Lip-mounted** - A manual clamp with set screw tightens firmly against the bucket edge.

## WARRANTY

Rockland Bucket Forks are guaranteed against failure due to defective design, workmanship, or materials for a period of one year or 2,000 hours.



Distributed by:

**ROCKLAND MANUFACTURING CO.**  
**P O BOX 5**  
**BEDFORD, PA 15522**  
[www.rocklandmfg.com](http://www.rocklandmfg.com)