



CG CANE GRAPPLE

CUT CANE HANDLING COSTS

HANDLE CANE WITH A WHEEL LOADER

Rockland CG Cane Grapples mounted on a wheel loader are the modern, low-cost solution to cane handling problems. Reduce cane handling costs dramatically by eliminating ground labor and revolving cranes. Capitalize on the speed and maneuverability of a wheel loader. Productivity is increased while payroll and equipment expenses are reduced by mounting a Rockland CG Cane Grapple on your wheel loader.



CG Cane Grapples are built to handle cane season after season without costly down time or aggravating repairs. They are built of high-strength, weight-saving, alloy steels to keep grapple weight to a minimum while delivering maximum payloads. Heavy-duty hydraulics, oversized clamp bearings and reinforcement at all critical stress areas underscore typical Rockland dedication to design excellence—a dedication that pays off on the job. Rockland CG Cane Grapples are available in capacities designed to match the lift and carry capacity of the loader upon which it will be mounted. Rockland CG Cane Grapples have proven themselves at cane mills around the world.

SPECIFICATIONS

[Click here to identify your machine category.](#)

Machine Category	20		30, 40		50, 60	
Model	CG-6		CG-8		CG-10	
	with kicker	without kicker	with kicker	without kicker	with kicker	without kicker
Backframe Height	42" 1067	42" 1067	57" 1448	57" 1448	57" 1448	57" 1448
Tine Clear Spacing	23" 584	23" 584	16" 406	16" 406	23" 584	23" 584
Overall Width	80" 2032	80" 2032	96" 2438	96" 2438	128" 3251	128" 3251
Kicker Width	36" 914	N/A	50" 1270	N/A	68" 1727	N/A
Tine Length	54" 1372	54" 1372	66" 1676	66" 1676	72" 1829	72" 1829
Clamp Width	50" 1270	50" 1270	59" 1499	59" 1499	78" 1981	78" 1981
Number of Tines	4	4	6	6	6	6
Weight lbs.	3900 1769	3100 1406	5400 2449	4200 1905	6000 2722	4700 2132

(metric)

Specifications Subject To Change Without Notice

MOUNTING INFORMATION

All CG Cane Grapples come complete with jumper hoses ready to mount in place of the standard bucket using factory pins or specified coupler brackets. A three-spool valve and boom arm piping are required to complete the installation.

WARRANTY

Rockland guarantees all CG Cane Grapples against failure due to defective design, workmanship, or materials for a period of one year or 2000 hours.



Distributed by:

ROCKLAND MANUFACTURING CO.
 P O BOX 5
 BEDFORD, PA 15522
www.rocklandmfg.com