



Compaction Wheels

TF TAMPER FOOT

FAST EFFECTIVE COMPACTION

Rockland Compaction Wheels are the fast and efficient way to compact backfilled trenches. The open rim design allows for maximum penetration into the trench to compact from the bottom up. The octagon pad design compacts 25% more surface area than the conventional pad with every pass.

More and more, job sites are requiring higher compaction densities. Get the job done economically, quickly and efficiently with a Rockland Compaction Wheel.



TF TAMPER FOOT

- Greater compaction in a wide range of soil conditions
- Specific models to fit your machine's application
- All Rockland wheels include a removable OEM mount
- Wain-Roy™ style and additional mounts available upon request
- Available for all sizes of excavators and backhoes



SOLID COMPACTION

MINI EXCAVATOR SPECIFICATIONS

Up to 15,000 lb.

MODEL	Approx. Wt.	Rim Qty	Foot Qty	Trench Width
WM6-1	300 lb.	1	10	6"
WM8-1	375 lb.	1	10	8"
WM12-3	425 lb.	3	30	12"
WM18-4	500 lb.	4	40	18"

Also available: 1/8 yd Wain-Roy™ option. Additional bolt-on top plates upon request.

RUBBER TIRED BACKHOE SPECIFICATIONS

11,000 - 25,000 lb.

MODEL	Approx. Wt.	Rim Qty	Foot Qty	Trench Width
WB8-1	625 lb.	1	10	8"
WB12-2	950 lb.	2	20	12"
WB18-3	1150 lb.	3	30	18"
WB24-3	1350 lb.	3	30	24"
WB36-4	1550 lb.	4	40	36"

Also available: 1/4 yd and 1/2 yd Wain-Roy™ option. Additional bolt-on top plates upon request.

HYDRAULIC EXCAVATOR SPECIFICATIONS

35,000 - 50,000 lb.

MODEL	Approx. Wt.	Rim Qty	Foot Qty	Trench Width
WI18-3	1700 lb.	3	30	18"
WI24-3	2100 lb.	3	30	24"
WI30-4	2400 lb.	4	40	30"
WI36-4	2500 lb.	4	40	36"

Also available: 1/2 yd and 3/4 yd Wain-Roy™ option. Additional bolt-on top plates upon request.

HYDRAULIC EXCAVATOR SPECIFICATIONS

50,000 - 110,000 lb.

MODEL	Approx. Wt.	Rim Qty	Foot Qty	Trench Width
WE18-3	2400 lb.	3	30	18"
WE24-3	2900 lb.	3	30	24"
WE30-4	3500 lb.	4	40	30"
WE36-4	3600 lb.	4	40	36"
WE48-6	4000 lb.	6	60	48"
WE60-7	4800 lb.	7	70	60"

Also available: 3/4 yd Wain-Roy™ option. Additional bolt-on top plates upon request.

MOUNTING INFORMATION

Rockland Compaction Wheels mount in place of the bucket, using the standard factory pins.



**ROCKLAND
MANUFACTURING CO.**

P.O. Box 5 | Bedford, PA 15522
800-458-3773 | www.rocklandmfg.com

**INCREASING PRODUCTIVITY
FOR MORE THAN 60 YEARS**

WARRANTY

Rockland Compaction Wheels are guaranteed against failure due to defective design, materials or workmanship for a period of one year or 2000 hours.

