



EX EXCAVATOR RAKES

**CLEAR LAND EFFICIENTLY
WITH AN EXCAVATOR**



Turn your excavator into an efficient land clearing machine with a Rockland Excavator Rake. The rake's long, tough, teeth are built of high-strength heat-treated alloy steel for years of heavy-duty land clearing service. They are curved for maximum rolling and sifting action. They project forward far enough so that loading land clearing debris is fast and efficient. If the job requires handling large capacity loads, use the EX Excavator Rake with a Rockland thumb to obtain maximum material handling capability.

EXCAVATOR RAKE SPECIFICATIONS

Machine Class	AA		A		B		C		D		E	
Excavator Weight Lbs.	10,001 to 21,000 4536 to 9526		21,001 to 32,000 9534 to 14515		32,001 to 49,000 14515 to 22246		49,001 to 60,000 22246 to 27240		60,001 to 78,000 27240 to 35412		78,001 to 101,000 35412 to 45854	
Raking Width	44"	1118	48"	1219	51"	1295	55"	1397	56"	1422	79"	2007
Clear Spacing	13"	330	14.5"	368	15"	381	16"	406	16"	406	23"	584
Number of Teeth	4		4		4		4		4		4	
Tooth Penetration	12"	305	16"	406	16"	406	20"	508	20"	508	20"	508
Tooth Thickness	1.25"	32	1.5"	38	1.5"	38	1.75"	44	2"	51	2.5"	64
Weight Lbs.	760	345	1240	562	1575	714	1950	885	2575	1168	3680	1669

(mm/kg)

Specifications are subject to change without notice.

Installation Information

All Rockland Excavator Rakes mount in place of the existing bucket using factory pins.

WARRANTY

Rockland Excavator Rakes are guaranteed against failure due to defective design, workmanship or materials for a period of one year or 2000 hours.



Distributed by:

**ROCKLAND MANUFACTURING CO.
P O BOX 5
BEDFORD, PA 15522
www.rocklandmfg.com**