



# MILLYARD GRAPPLES

**ML-W WIDE CLAMP**  
**ML-2 DUAL CLAMP**



## **DESIGNED FOR YEARS OF TROUBLE FREE, DEPENDABLE SERVICE**

Rockland designed the Millyard Grapple to accommodate the many needs of the modern millyard. Now you can specify a grapple with a clamp that suits your operation.

The ML-W has a powerful, wide clamp that closes between the tines all the way to the frame. The ML-2 has dual clamps that can be ordered either to close on the tine tips or bypass the tines and close against the frame.

The rugged Rockland Millyard Grapple is built of high-strength, weight-saving alloy steels. These steels keep grapple weight to a minimum while increasing strength for years of dependable service. Clamps pivot on heavy-duty, oversized pins and bushings. Pivot bearings are extra wide for long life.

Rockland hydraulics are first class. We use only top quality, high-pressure hoses and fittings. Rockland hydraulic cylinders feature heavy-duty, chrome plated induction-hardened piston rods. Cylinders are put together with top quality seals, and are designed to absorb the heavy shock loads that are frequently encountered when handling logs.

Whether you specify the ML-W or the ML-2, you'll definitely agree—the Rockland Millyard Grapple was designed to guarantee years of trouble-free, dependable service.

# MILLYARD GRAPPLE

**ML-W WIDE CLAMP  
ML-2 DUAL CLAMP**

## SPECIFICATIONS

[Click here to identify your machine category.](#)

Machine Category	20	30	40	50	60	70
<b>Overall Width</b>	<b>80"</b> 2032	<b>84"</b> 2134	<b>84"</b> 2134	<b>87"</b> 2210	<b>92"</b> 2337	<b>108"</b> 2743
<b>Tine Width</b>	<b>3"</b> 76	<b>3.5"</b> 89	<b>4.5"</b> 114	<b>5"</b> 127	<b>6"</b> 153	<b>8"</b> 203
<b>Min. Clamp Opening</b>	<b>10"</b> 254	<b>12"</b> 305	<b>12"</b> 305	<b>14"</b> 356	<b>14"</b> 356	<b>18"</b> 457
<b>Height to Clamp Pivot</b>	<b>54"</b> 1372	<b>54"</b> 1372	<b>60"</b> 1524	<b>66"</b> 1676	<b>72"</b> 1829	<b>84"</b> 2134
<b>Max. Clamp Opening</b>	<b>102"</b> 2591	<b>106"</b> 2692	<b>112"</b> 2845	<b>114"</b> 2896	<b>115"</b> 2921	<b>130"</b> 3302
<b>Tine Length to Backframe</b>	<b>48"</b> 1219	<b>54"</b> 1372	<b>54"</b> 1372	<b>60"</b> 1524	<b>72"</b> 1829	<b>84"</b> 2134
<b>Weight ML-W lbs.</b>	<b>2600</b> 1179	<b>3200</b> 1452	<b>3400</b> 1542	<b>5300</b> 2404	<b>5800</b> 2631	<b>7500</b> 3402
<b>Weight ML-2 lbs.</b>	<b>2400</b> 1089	<b>2900</b> 1315	<b>3100</b> 1406	<b>5000</b> 2268	<b>5400</b> 2449	<b>7000</b> 3175

(mm/kg)

Specifications subject to change without notice.

## MOUNTING INFORMATION

All Rockland grapples mount in place of the standard bucket using factory pins or specified coupler brackets. Grapples are equipped with all necessary piping and hydraulics including jumper hoses which connect to the loader lift arm piping. A three-spool valve and lift arm piping are required on the loader to complete the installation.



## WARRANTY

Rockland Millyard Grapples are guaranteed against failure due to defective design, workmanship or materials for a period of one year or 2,000 hours.



**Distributed by:**

**ROCKLAND MANUFACTURING CO.**  
P O BOX 5  
BEDFORD, PA 15522  
[www.rocklandmfg.com](http://www.rocklandmfg.com)