



SG SAND AND GRAVEL BUCKETS

HANDLE SAND AND GRAVEL EFFICIENTLY WITH YOUR LOADER

Standard buckets don't always stand up to sand and gravel applications. That's why Rockland developed a line of buckets just for sand and gravel handling.

All Rockland SG Sand and Gravel Buckets feature a flat bottom design that makes loading easier - difficulty penetrating piles of material is eliminated. Rockland SG Sand and Gravel Buckets are equipped with weld-on, replaceable skid shoes and bolt-on cutting edges.

A Rockland SG Sand and Gravel Bucket will last longer and can be configured to carry more than standard buckets. Slope bottom models are available at no extra charge. Bolt-on wear plates, teeth, and hardfacing are also available to make the bucket extra tough.



When you're handling sand or gravel, request a Rockland SG Sand and Gravel Buckets that is designed to increase productivity and deliver years of dependable service.



FEATURES

- Flat bottom design for fast easy stock-pile penetration.
- Slope bottom design available at no extra charge.
- Full length, replaceable wear strips.
- Straight sidecutters.
- Equipped with bolt-on reversible cutting edges or optional bolt-on adapters and segments.
- Covered by Rockland's no nonsense warranty.

SPECIFICATIONS

WHEEL LOADER SPECIFICATIONS

Machine Category	5	5,10	10	10	20	20	20,30	30	30,40
Capacity YD ³	1 .76	1.25 .95	1.5 1.14	1.75 1.33	2 1.52	2.25 1.72	2.5 1.19	2.75 2.1	3 2.29
Width	94" 2388	94" 2388	94" 2388	94" 2388	94" 2388	94" 2388	96" 2438	108" 2743	112" 2845
Weight lbs.	1495 678	1595 723	1695 769	1845 837	2135 968	2285 1036	2460 1116	2750 1247	3020 1370

Machine Category	40	40	40	40,50	50	50	50	50,60	60
Capacity YD ³	3.25 2.48	3.5 2.67	3.75 2.86	4 3.05	4.25 3.24	4.5 3.44	4.75 3.63	5 3.82	5.5 4.2
Width	112" 2845	116" 2946	116" 2946	120" 3048	120" 3048	120" 3048	120" 3048	130" 3302	136" 3454
Weight lbs.	3295 1495	3600 1633	3800 1724	4080 1851	4230 1919	4380 1987	4530 2055	4980 2259	5310 2409

Machine Category	60,70	60,70	70	70	70,80	80	80	80	80,90
Capacity YD ³	6 4.58	6.5 4.96	7 5.35	7.5 5.73	8 6.11	8.5 6.49	9 6.88	9.5 7.26	10 7.64
Width	142" 3607	142" 3607	142" 3607	148" 3759	148" 3759	154" 3912	154" 3912	154" 3912	168" 4267
Weight lbs.	5750 2608	6350 2880	7050 3198	7275 3300	7675 3481	8380 3801	9180 4164	9430 4277	9510 4314

(mm/kg)

Specifications subject to change without notice.

CRAWLER LOADER SPECIFICATIONS

Machine Category	5	5	5,10	10	10	10,20	20,30	30	40
Capacity YD ³	.75 .57	.875 .66	1 .76	1.25 .95	1.375 1.05	1.5 1.14	1.75 1.33	2 1.52	2.25 1.72
Width	66" 1676	72" 1829	72" 1829	72" 1829	72" 1829	79" 2007	82" 1736	86" 2184	88" 2235
Weight lbs.	940 426	1040 472	1130 513	1375 624	1495 678	1930 875	2270 1030	2335 1059	2500 1134

Machine Category	40,50	50	50	60	60	60
Capacity YD ³	2.5 1.19	2.75 2.1	3 2.29	3.25 2.48	3.5 2.67	3.75 2.86
Width	90" 2286	96" 2438	100" 2540	101" 2565	103" 2616	103" 2616
Weight lbs.	2630 1193	3275 1486	3565 1617	3845 1744	4220 1914	4370 1982

(mm/kg)

Specifications subject to change without notice.

MOUNTING INFORMATION

Rockland SG Sand and Gravel Buckets mount in place of the standard bucket with factory pins or specified coupler brackets.

WARRANTY

Rockland SG Sand and Gravel Buckets are guaranteed against failure due to defective design, materials, or workmanship for a period of one year or 2,000 hours.



Distributed by:

ROCKLAND MANUFACTURING CO.
P O BOX 5
BEDFORD, PA 15522
800-458-3773
www.rocklandmfg.com