



SUPER SORT BUCKETS

SORT THE QUICK AND EASY WAY

THIS METHOD MAKES SENSE!

Rockland Super Sort Buckets make sorting and separating easier than ever. They eliminate the need for vibrating screens and material rehandling. Now you can dig and sort with one machine during the loading cycle. The efficiency is amazing and the savings are tremendous!



Ready to Dig

With the separator in the retracted position, the Rockland Super Sort Bucket loads just as quickly and easily as a conventional bucket. Separating is done as the bucket is raised.



Lift and Separate

Two heavy-duty hydraulic cylinders power the separator up through the load, sorting as it lifts. Some materials may require an extra bump or two.



Dump

The bucket is dumped first. Sorted material is dumped next by retracting the separator. It dumps just like a normal bucket. After dumping, the separator is in the retracted position ready to dig again.

Available for Loaders, Excavators, Tractor Loader Backhoes and Skid Steer Loaders



Super Sort Buckets are tough enough to sort rocks day after day for years. Special applications are a breeze!

Loaders equipped with Super Sort Buckets are very productive because digging ability is not sacrificed and sorting is done during the digging cycle.

**Get a video today—
seeing is believing!**



SUPER SORT BUCKETS

The Super Sort Bucket was originally developed to sort rocks from in-place base material for roadbuilding. These revolutionary buckets eliminated the need to truck in rock-free base material. The savings were enormous.

Rockland Super Sort Buckets are ideal for separating rocks from backfill material. Installed on a Tractor Loader Backhoe, or on a Skid Steer Loader, they are also ideal for landscaping and site preparation. The possibilities are unlimited. New applications are being discovered every week.

The specifications below are for typical heavy sorting applications. The Super Sort can be supplied to almost any clear spacing required. Weights will vary depending upon application and clear spacing.

LOADER SPECIFICATIONS - standard 10" clear spacing

| Cubic Yard Capacity Super Sort Buckets | | 2.5 | | 3 | | 3.5 | | 4 | | 4.5 | | 5 | | 5.5 | | 6 | |
|---|-----|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| For Heavy Rock | lbs | 3455 | 1567 | 4520 | 2051 | 4975 | 2257 | 5720 | 2595 | 6265 | 2842 | 7735 | 3509 | 8150 | 3697 | 9095 | 4125 |
| Separator Only | lbs | 860 | 390 | 1105 | 501 | 1130 | 513 | 1260 | 572 | 1305 | 592 | 1785 | 810 | 1800 | 816 | 1945 | 882 |
| For Rehandling | lbs | 2895 | 1313 | 3420 | 1551 | 4265 | 1935 | 4715 | 2139 | 5080 | 2304 | 5500 | 2495 | 6150 | 2790 | 6705 | 3041 |
| Separator Only | lbs | 795 | 361 | 870 | 395 | 1165 | 529 | 1215 | 551 | 1280 | 581 | 1400 | 635 | 1750 | 794 | 1905 | 864 |
| For Light Material | lbs | 2270 | 1030 | 2500 | 1134 | 3060 | 1388 | 3300 | 1497 | 3610 | 1637 | 4275 | 1939 | 4480 | 2032 | 5115 | 2320 |
| Separator Only | lbs | 570 | 259 | 600 | 272 | 760 | 345 | 800 | 363 | 810 | 367 | 1175 | 533 | 1180 | 535 | 1190 | 540 |

EXCAVATOR SPECIFICATIONS - standard 10" clear spacing

| Cubic Yard Capacity Super Sort Buckets | | .5 | | .75 | | 1 | | 1.25 | | 1.5 | | 1.75 | | 2 | | 2.5 | | 3 | |
|---|-----|------|-----|------|-----|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| For Heavy Rock | lbs | 1365 | 619 | 1920 | 871 | 2325 | 1055 | 2845 | 1290 | 3245 | 1472 | 3680 | 1669 | 4230 | 1919 | 4740 | 2150 | 4935 | 2239 |
| Separator Only | lbs | 275 | 125 | 290 | 132 | 305 | 138 | 495 | 225 | 545 | 247 | 700 | 318 | 740 | 336 | 750 | 340 | 815 | 370 |
| For Rehandling | lbs | 1165 | 528 | 1550 | 703 | 1785 | 810 | 2265 | 1027 | 2590 | 1175 | 3325 | 1508 | 3360 | 1524 | 3920 | 1778 | 4470 | 2028 |
| Separator Only | lbs | 290 | 132 | 300 | 136 | 335 | 152 | 505 | 229 | 520 | 236 | 700 | 318 | 735 | 333 | 755 | 342 | 850 | 386 |

TRACTOR LOADER BACKHOE SPECIFICATIONS - standard 6" clear spacing

| Cubic Yard Capacity Super Sort Buckets | | .5 | | .75 | | 1 | | 1.2 | | 1.5 | |
|---|-----|-----|-----|-----|-----|------|-----|------|-----|------|-----|
| For Rehandling | lbs | 755 | 342 | 855 | 388 | 1280 | 581 | 1510 | 185 | 1830 | 830 |
| Separator Only | lbs | 275 | 125 | 305 | 138 | 470 | 213 | 530 | 240 | 615 | 278 |

SKID STEER LOADER SPECIFICATIONS - standard 6" clear spacing

| Cubic Yard Capacity Super Sort Buckets | | 6 | | 10 | | 12 | | 15 | | 18 | | 20 | |
|---|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| For Rehandling | lbs | 260 | 118 | 495 | 225 | 550 | 249 | 655 | 297 | 700 | 318 | 725 | 329 |
| Separator Only | lbs | 130 | 59 | 150 | 68 | 175 | 79 | 245 | 111 | 250 | 113 | 255 | 116 |

(mm/kg)

Specifications subject to change without notice.

MOUNTING INFORMATION

Super Sort Buckets mount on the loader using standard factory pins and come complete with jumper hoses. Loaders must be equipped with a three-spool valve and lift arm piping.

WARRANTY

Rockland Super Sort Buckets are guaranteed against failure due to defective design, workmanship, or materials for a period of one year or 2,000 hours.



Distributed by:

ROCKLAND MANUFACTURING CO.
P O BOX 5
BEDFORD, PA 15522
www.rocklandmfg.com